

NA-iTTL NIKON ELECTRONIC FLASH EF-530 DG SUPER

It is compatible with the new i-TTL system. Availability of TTL Auto depends on the lens, but this system can be used with all Nikon camera models. It is possible to use Manual Flash as well as distance-priority manual flash, which is specific to Nikon (except D1X and D1H cameras). Red-eye reduction control, Rear-Curtain Synchro and Exposure Compensation functions are also available (except with some camera models). Manual Flash Functions, as well as Wireless Flash Functions are also available (except with some camera models). Manual switching of the amount of light is from 1/1 to 1/64. Auto-Power Off function shuts off the power if the flashgun is not used for 80 seconds.

	TTL Auto *1	Autozoom Head	Distance Priority Manual Flash	AF Auxiliary Lamp	Red-Eye Reduction Function	Wireless Flash	Designated Slave Flash *4	Normal Slave Flash	Rear-Curtain Synchro	Exposure Compensation Function
F3	TTL Flash Control	×	✓	×	×	×	✓	✓	×	×
F4 Series	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓	✓	×	✓	✓	×	✓
F5	3D-Multi BL Flash Control, Multi BL Flash Control	✓	✓	✓ *2	×	×	✓	✓	✓	✓
F6	i-TTL-BL Flash Control, Multi BL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *5	✓	✓
F50D (N50)	TTL-BL Flash Control, Simple TTL-BL Flash Control	×	✓	×	×	×	✓	✓	×	×
F60D (N60)	TTL-BL Flash Control, Simple TTL-BL Flash Control	×	✓	✓	×	×	✓	✓	×	×
F70D (N70)	3D-Multi BL Flash Control, Multi BL Flash Control	✓	✓	✓	✓	×	✓	✓	✓	✓
F80 (N80) Series	3D-Multi BL Flash Control, Multi BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓	✓	✓
F90X (N90) Series	3D-Multi BL Flash Control, Multi BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓	✓	✓
F100	3D-Multi BL Flash Control, Multi BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓	✓	✓
F-301 (N2000)	TTL Program Flash, TTL Flash Control	×	✓	✓ *3	×	×	✓	✓	×	×
F-401 (N4004)	TTL Program Flash, TTL Flash Control	×	✓	✓	×	×	✓	✓	×	×
F-401S (N4004S)	TTL Program Flash, TTL Flash Control	×	✓	✓	×	×	✓	✓	×	×
F-401X (N5005)	TTL Program Flash, TTL Flash Control	×	✓	✓	×	×	✓	✓	×	×
F-501 (N2020)	TTL Program Flash, TTL Flash Control	×	✓	✓	×	×	✓	✓	×	×
F-601 (N6006)	TTL Program Flash, TTL Flash Control	×	✓	✓	×	×	✓	✓	✓	✓
F-601M (N6000)	TTL-BL Flash Control, Simple TTL-BL Flash Control	×	✓	✓	×	×	✓	✓	✓	✓
F-801 (N8008)	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓	×	×	✓	✓	✓	✓
F-801S (N8008S)	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓	×	×	✓	✓	✓	✓
FA	TTL Flash Control	×	✓	×	×	×	✓	✓	×	×
FE2	TTL Flash Control	×	✓	×	×	×	✓	✓	×	×
FG	TTL Flash Control	×	✓	×	×	×	✓	✓	×	×
PRONEA600i	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓		×	×	✓	✓	✓	✓
U (F65/N65)	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓ *2	×	×	✓	✓	✓	✓
Us (F55/N55)	TTL-BL Flash Control, Simple TTL-BL Flash Control	×	✓	×	×	×	✓	✓	×	×
U2 (F75/N75)	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓	✓	✓
D1	TTL-BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓ *5	✓	✓
D1H	3D-Multi BL Flash Control, Multi BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓ *5	✓	✓
D1X	3D-Multi BL Flash Control, Multi BL Flash Control, Simple D-TTL-BL Flash Control	✓	✓	✓ *2	✓	×	✓	✓ *5	✓	✓
D2X	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *5	✓	✓
D2Xs	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *5	✓	✓
D2H	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *5	✓	✓
D2Hs	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *5	✓	✓
D3	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *5	✓	✓

NA-iTTL NIKON ELECTRONIC FLASH EF-530 DG SUPER

It is compatible with the new iTTL system. Availability of TTL Auto depends on the lens, but this system can be used with all Nikon camera models. It is possible to use Manual Flash as well as distance-priority manual flash, which is specific to Nikon (except D1X and D1H cameras). Red-eye reduction control, Rear-Curtain Synchro and Exposure Compensation functions are also available (except with some camera models). Manual Flash Functions, as well as Wireless Flash Functions are also available (except with some camera models). Manual switching of the amount of light is from 1/1 to 1/64. Auto-Power Off function shuts off the power if the flashgun is not used for 80 seconds.

	TTL Auto *1	Autozoom Head	Distance Priority Manual Flash	AF Auxiliary Lamp	Red-Eye Reduction Function	Wireless Flash	Designated Slave Flash *4	Normal Slave Flash	Rear-Curtain Synchro	Exposure Compensation Function
D3X	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *5	✓	✓
D100	3D-Multi BL Flash Control, Multi BL Flash Control, Standard D-TTL Flash Control	✓	✓	✓ *2	✓	×	✓	✓ *6	✓	✓
D200	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D300	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D700	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D5000	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D90	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D80	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D70	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D70s	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓
D60	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *6	✓	✓
D50	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *6	✓	✓
D40	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *6	✓	✓
D40x	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓ *7	✓	✓ *6	✓	✓
FinePix S1 Pro	TTL-BL Flash Control	×	✓	✓ *2	×	×	✓	✓	×	×
FinePix S2 Pro	3D-Multi BL Flash Control, Multi BL Flash Control	×	✓	✓ *2	✓	×	✓	✓	✓	✓
FinePix S3 Pro	3D-Multi BL Flash Control, Multi BL Flash Control, D-TTL Flash Control	✓	✓	✓ *2	✓	×	✓	✓ *6	✓	✓
FinePix S5 Pro	i-TTL Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓ *2	✓	✓	✓	✓ *6	✓	✓

*1: Flash Exposure function changes by the lens and metering mode. For details, please refer to your camera's instruction manual.

*2: It can be used if center focus is selected.

*3: It can be used only when AF lenses are attached.

*4: It can be used as a Master unit only by using two DG SUPER units.

*5: Please set your Master unit to Manual Flash mode.

*6: Built-in flash cannot be used. Please set your Master unit to Manual Flash mode.

*7: It can only be used if two DG SUPER units are used.