

SA-STTL SIGMA ELECTRONIC FLASH EF-530 DG SUPER

It is possible to use TTL Auto, Manual Flash, Autozoom Head, AF Auxiliary Lamp, Red-eye Reduction function, High-speed synchro (FP), Wireless Flash (except SD9), Designated Slave Flash, Normal Slave Flash, Rear-curtain Synchro Flash, Exposure Compensation Function, Multi Flash and Modeling Flash functions. Manual switching of the amount of light is from 1/1 to 1/128. Auto Power-Off function shuts off 300 seconds after use.

	TTL Auto	Autozoom Head	AF Auxiliary Lamp	Red-Eye Reduction Function	High-Speed Synchro	Wireless Flash	Designated Slave Flash*3	Normal Slave Flash	Rear-Curtain Synchro	Exposure Compensation Function
SA-300	TTL	✓	✓	✓	×	✓ *1	✓	✓	✓ *4	✓
SA-300N	TTL	✓	✓	✓	✓	✓ *1	✓	✓	✓ *4	✓
SA-5	TTL	✓	✓	✓	✓	✓ *1	✓	✓	✓ *4	✓
SA-7	TTL	✓	✓	✓	✓	✓ *1	✓	✓	✓	✓
SA-7N	TTL	✓	✓	✓	✓	✓ *1	✓	✓	✓	✓
SA-9	TTL	✓	✓	✓	✓	✓ *1	✓	✓	✓	✓
SD9	STTL	✓	✓	✓	✓	×	✓	✓ *5	✓ *5	✓
SD10	STTL	✓	✓	✓	✓	✓ *2	✓	✓ *5	✓ *5	✓
SD14	STTL	✓	✓	✓	✓	✓	✓	✓ *6	✓ *5	✓
RICOH GR DIGITAL	AUTO	×	×	×	×	×	×	×	×	×
RICOH GR DIGITAL II	AUTO	×	×	×	×	×	×	×	×	×

*1: The built-in flash will be used as the control flash.

*2: It can be used when two DG SUPER units are used.

*3: It can be used as a Master unit only by using two DG SUPER units.

*4: SA-300,SA-300N,SA-5 cannot be used in AUTO mode.

*5: Please set your Master unit to Manual flash mode.

*6: Built-in flash cannot be used. Please set your Master unit to Manual Flash mode.