

SIGMA

Compatibility Table

EO-ETTL II CANON ELECTRONIC FLASH EF-610 DG ST

Operation of the TTL Auto system varies between camera models (If E-TTL II, E-TTL and TTL Automatic Exposure can be used then A-TTL Automatic exposure is not possible). It is possible to use Manual Flash, Autozoom Head, AF Auxiliary Lamp. Manual flash mode with two levels: Full power and 1/16 power. Auto Power-Off function shuts off 90 seconds after use.

	TTL Auto	Autozoom Head	Manual Flash	AF Auxiliary Lamp
EOS-1D	E-TTL	✓	✓	✓
EOS-1D Mark II	E-TTL II	✓	✓	✓
EOS-1D Mark II N	E-TTL II	✓	✓	✓
EOS-1D Mark III	E-TTL II	✓	✓	✓
EOS-1D Mark IV	E-TTL II	✓	✓	✓
EOS-1D X	E-TTL II	✓	✓	✓
EOS-1Ds	E-TTL	✓	✓	✓
EOS-1Ds Mark II	E-TTL II	✓	✓	✓
EOS-1Ds Mark III	E-TTL II	✓	✓	✓
EOS 5D	E-TTL II	✓	✓	✓
EOS 5D Mark II	E-TTL II	✓	✓	✓
EOS 5D Mark III	E-TTL II	✓	✓	✓
EOS 5Ds	E-TTL II	✓	✓	✓
EOS 5DsR	E-TTL II	✓	✓	✓
EOS 6D	E-TTL II	✓	✓	✓
EOS 7D	E-TTL II	✓	✓	✓
EOS 7DMarkII	E-TTL II	✓	✓	✓
EOS 10D	E-TTL	✓	✓	✓
EOS 20D	E-TTL II	✓	✓	✓
EOS 30D	E-TTL II	✓	✓	✓
EOS 40D	E-TTL II	✓	✓	✓
EOS 50D	E-TTL II	✓	✓	✓
EOS 60D	E-TTL II	✓	✓	✓
EOS 70D	E-TTL II	✓	✓	✓
EOS D30	E-TTL	✓	✓	✓
EOS D60	E-TTL	✓	✓	✓
EOS 8000D, EOS REBEL T6s, EOS 7600D	E-TTL II	✓	✓	✓
EOS Kiss Digital, EOS Digital REBEL, EOS 300D Digital	E-TTL	✓	✓	✓
EOS Kiss Digital N, EOS Digital REBEL XT, EOS 350D Digital	E-TTL II	✓	✓	✓
EOS Kiss Digital X, EOS Digital REBEL Xti, EOS 400D Digital	E-TTL II	✓	✓	✓
EOS Kiss X2, EOS REBEL Xsi, EOS 4500D	E-TTL II	✓	✓	✓
EOS Kiss X3, EOS REBEL T1i, EOS 5000D	E-TTL II	✓	✓	✓
EOS Kiss F, EOS REBEL XS, EOS 1000D	E-TTL II	✓	✓	✓
EOS Kiss X4, EOS REBEL T2i, EOS 5500D	E-TTL II	✓	✓	✓
EOS Kiss X5, EOS REBEL T3i, EOS 6000D	E-TTL II	✓	✓	✓
EOS Kiss X6i, EOS REBEL T4i, EOS 6500D	E-TTL II	✓	✓	✓
EOS Kiss X7i, EOS REBEL T5i, EOS 7000D	E-TTL II	✓	✓	✓
EOS Kiss X7, EOS REBEL SL1, EOS 1000D	E-TTL II	✓	✓	✓
EOS Kiss X8i, EOS REBEL T6i, EOS 7500D	E-TTL II	✓	✓	✓
EOS Kiss X50, EOS REBEL T3, EOS 11000D	E-TTL II	✓	✓	✓
EOS Kiss X70, EOS REBEL T5, EOS 12000D	E-TTL II	✓	✓	✓