

SIGMA

Compatibility Table

NA-iTTL NIKON ELECTRONIC FLASH EF-610 DG ST

This flashgun is compatible with Nikon's new i-TTL system. TTL Auto varies depending on the lenses in use, but it works on all cameras. It is possible to use Manual Flash as well. Available with cameras providing Red-eye reduction control only. Manual flash mode with two levels: Full power and 1/16 power. Auto Power-Off function shuts off 80 seconds after use.

	TTL Auto *1	Autozoom Head	Manual Flash	AF Auxiliary Lamp *2	Red-Eye ReductionFunction
D1	3D-Multi BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓	✓
D1H	3D-Multi BL Flash Control, Multi BL Flash Control, Simple TTL-BL Flash Control	✓	✓	✓	✓
D1X	3D-Multi BL Flash Control, Multi BL Flash Control, Simple D-TTL-BL Flash Control	✓	✓	✓	✓
D2X	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D2Xs	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D2H	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D2Hs	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3X	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3s	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D4	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D4s	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D100	3D-Multi BL Flash Control, Multi BL Flash Control, Standard D-TTL	✓	✓	✓	✓
D200	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D300	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D300s	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D700	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D750	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D800 / D800E	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓

SIGMA

Compatibility Table

NA-iTTL NIKON ELECTRONIC FLASH EF-610 DG ST

This flashgun is compatible with Nikon's new i-TTL system. TTL Auto varies depending on the lenses in use, but it works on all cameras. It is possible to use Manual Flash as well. Available with cameras providing Red-eye reduction control only. Manual flash mode with two levels: Full power and 1/16 power. Auto Power-Off function shuts off 80 seconds after use.

	TTL Auto *1	Autozoom Head	Manual Flash	AF Auxiliary Lamp *2	Red-Eye ReductionFunction
D810	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D810A	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
Df	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3000	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3100	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3200	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D3300	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D5000	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D5100	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D5200	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D5300	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D5500	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D7000	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D7100	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D7200	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D40	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D40x	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D50	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D60	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D70	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D70s	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓

SIGMA

Compatibility Table

NA-iTTL NIKON ELECTRONIC FLASH EF-610 DG ST

This flashgun is compatible with Nikon's new i-TTL system. TTL Auto varies depending on the lenses in use, but it works on all cameras. It is possible to use Manual Flash as well. Available with cameras providing Red-eye reduction control only. Manual flash mode with two levels: Full power and 1/16 power. Auto Power-Off function shuts off 80 seconds after use.

	TTL Auto *1	Autozoom Head	Manual Flash	AF Auxiliary Lamp *2	Red-Eye ReductionFunction
D80	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓
D90	i-Multi BL Flash Control, Standard i-TTL Flash Control	✓	✓	✓	✓

*1 Flash Exposure function changes by the lens, and metering mode. For details, please refer to instruction manual of your camera.

*2 It can be used, if center focus is selected.