

Compatibility Table

PA-PTTL PENTAX ELECTRONIC FLASH MACRO EM-140 DG

TTL Auto, Manual Flash, Rear-Curtain Synchro, Multi Flash functions and Modeling Flash, High-Speed Synchro, Wireless Flash, Exposure Compensation Function and the flash ratio adjustment for the left or right flash tube can be used. Manual switching of the amount of light is 1/1 - 1/64; Auto Power Off function shuts off 180 seconds after use.

	TTL Auto	Manual Flash	High-Speed Synchro (FP)	Wireless Flash *1	Rear-Curtain Synchro	Exposure Compensation Function
*istD	P-TTL	✓	✓	✓	✓	✓
*istDS	P-TTL	✓	✓	✓	✓	✓
*istDS2	P-TTL	✓	✓	✓	✓	✓
*istDL	P-TTL	✓	✓	✓	✓	✓
*istDL2	P-TTL	✓	✓	✓	✓	✓
K10D	P-TTL	✓	✓	✓	✓	✓
K20D	P-TTL	✓	✓	✓	✓	✓
K30	P-TTL	✓	✓	✓	✓	✓
K50	P-TTL	✓	✓	✓	✓	✓
K100D / K110D	P-TTL	✓	✓	✓	✓	✓
K100D Super	P-TTL	✓	✓	✓	✓	✓
K200D	P-TTL	✓	✓	✓	✓	✓
K-m	P-TTL	✓	✓	✓	✓	✓
K-r	P-TTL	✓	✓	✓	✓	✓
K-x	P-TTL	✓	✓	✓	✓	✓
K-5	P-TTL	✓	✓	✓	✓	✓
K-5II / K-5IIs	P-TTL	✓	✓	✓	✓	✓
K-7	P-TTL	✓	✓	✓	✓	✓

*1 To function as slave controller unit.