

## Compatibility Table

### SA-STTL SIGMA ELECTRONIC FLASH MACRO EM-140 DG

It is possible to use TTL Auto, Manual Flash, AF Auxiliary Lamp, High-speed synchro (FP), Wireless Flash (except SD9), Designated Slave Flash, Rear-curtain Synchro Flash, Exposure Compensation Function, Multi-Flash, Modeling Flash functions. Manual switching of the amount of light is from 1/1 to 1/64. Auto Power-Off function shuts off 300 seconds after use.

|              | TTL<br>Auto | High-Speed<br>Synchro | Manual<br>Flash | Wireless<br>Flash *1 | Designated<br>Slave Flash *1 | Rear-Curtain<br>Synchro | Exposure<br>Compensation<br>Function |
|--------------|-------------|-----------------------|-----------------|----------------------|------------------------------|-------------------------|--------------------------------------|
| SD9          | STTL        | ✓                     | ✓               | ×                    | ✓                            | ✓ *2                    | ✓                                    |
| SD10         | STTL        | ✓                     | ✓               | ✓                    | ✓                            | ✓ *2                    | ✓                                    |
| SD14         | STTL        | ✓                     | ✓               | ✓                    | ✓                            | ✓ *2                    | ✓                                    |
| SD15         | STTL        | ✓                     | ✓               | ✓                    | ✓                            | ✓ *2                    | ✓                                    |
| SD1          | STTL        | ✓                     | ✓               | ✓                    | ✓                            | ✓ *2                    | ✓                                    |
| SD1 Merrill  | STTL        | ✓                     | ✓               | ✓                    | ✓                            | ✓ *2                    | ✓                                    |
| sd Quattro   | STTL        | ✓ *4                  | ✓               | ✓                    | ✓                            | ✓ *2, *4                | ✓                                    |
| sd Quattro H | STTL        | ✓ *4                  | ✓               | ✓                    | ✓                            | ✓ *2, *4                | ✓                                    |
| DP3Merrill   | STTL        | ×                     | ✓               | ×                    | ×                            | ×                       | ✓ *3                                 |
| dp3 Quattro  | STTL        | ×                     | ✓               | ×                    | ×                            | ×                       | ✓ *3                                 |
| fp           | STTL        | ×                     | ✓               | ×                    | ×                            | ✓ *2, *4                | ✓                                    |

\*1 It can be used as Master unit only.

\*2 Manual Flash only.

\*3 This setting is only available on camera.

\*4 This setting is only available on flash.